



HWO/SNUBBING UNIT 600K

Service > Hydraulic Workover > Equipment



The reliable and flexible 600K HWO/Snubbing Unit has been designed for all well situations: live/dead, onshore/offshore. The 600K satisfies your need for high quality, safe and efficient Snubbing or Workover operations in any environment.

The jointed work string is handled by means of 4 hydraulic cylinders (3m stroke). The use of hydraulic cylinders allows perfect control over work string movements and makes it easy to use all types of downhole tools.

Advantages & Characteristics:

- Unique “Slip bowl Interlock System”
- Small footprint
- Flexible
- Mobile
- Excellent cost/quality ratio
- Multi-purpose application

Technical Data

600K HWO/Snubbing unit

Max. pull capacity	600,000 lbs	270.000 kg
Max. push capacity	263,000 lbs	118.000 kg
Rotary torque	20,000 ft.lbs	27.000 Nm
Stroke	10 ft	3 m
Through bore	11 1/8" (Snubbing)	283 mm (Snubbing)
	13 5/8" (HWO)	346 mm (HWO)
Slip bowls	600.000 lbs	270.000 kg
Gin Pole	2 x 5.500 lbs	2 x 2500 kg
Unit total weight	80.000 lbs	40.000 kg

Operational activities:

- Handling all types of completions
- Live/Dead well operations
- Packer setting/milling
- Well clean out
- Live well Fishing operations
- Underbalance installation of liners
- Remedial operations
- Installation of velocity strings

Do NOT kill your well – Save your formation!
Exploit the benefits of our underbalance (UB) operations

www.bpc.nl